



ISOVER ACOUSTIC PARTITION ROLL (APR 1200)

Acoustic insulation for drylining systems and floors

Isover Acoustic Partition Roll (APR1200) is a 600mm wide glass mineral wool designed to fit between standard stud spacings.

Isover Acoustic Partition Roll (APR1200) provides high levels of acoustic insulation in walls and floors to meet acoustic requirements in domestic and non-residential applications.



Features and Benefits

Acoustic

Excellent acoustic performance
Reduces unwanted noise when used in light weight partitions and internal floors.

British Gypsum SpecSure® Warranty
Guaranteed lifetime performance when used as a part of British Gypsum drywall and acoustic floor systems.

Non-combustible
Isover glass mineral wool insulation has an A1 Euroclass fire rating - the best attainable.

Protected planet
BES 6001 - The Framework Standard for Responsible Sourcing - Rating, "Good"

Recycled glass

Recycled content
Manufactured from up to 86% recycled glass.

Product Specification

Product code	Thickness (mm)	Width (mm)	Length (mm)	Pack area (m ²)	Packs per pallet	Pallet area (m ²)
5200625577	25	2 x 600	20000	24.00	24	576.00
5200625578	50	2 x 600	13000	15.60	24	374.40
5200625579	65	2 x 600	10000	12.00	24	288.00
5200625580	75	2 x 600	12200	14.64	24	351.36
5200625581	100	2 x 600	9170	11.00	24	264.00



CHARACTERISTICS

Characteristic	Description
Fire	Euroclass A1 fire rating when classified to BS EN 13501-1.
Environmental	All Isover products are manufactured under Environmental Management System - ISO 14001. BES 6001 - The Framework Standard for Responsible Sourcing - Rating, "Good". The manufacturing process does not use or contain CFC's, HCFC's or other damaging gases.
BRE statements	Isover APR 1200 corresponds to the BRE Global Green Guide online generic specification "Glass wool insulation", thicknesses 75mm and 100mm - density 12kg/m ³ , ref. 815320001, thicknesses 25mm, 50mm and 65mm - density 24kg/m ³ , ref. 815320002 which achieve summary ratings of A+ within Domestic, Health, Industrial, Commercial, Retail, Education. NB: The densities stated above are part of generic BRE classifications and do not reflect the exact specification of the products.
Quality	All Isover products are manufactured under Quality Management Standard - ISO 9001.
Building regulations	Helps to meet the requirements of UK acoustic building regulations.
Recycled content	Isover glass mineral wool insulation is manufactured from up to 86% recycled glass. This makes Isover one of the most environmentally sustainable insulation products on the market today.
Durability	Made from rot-proof non-hygroscopic materials. Will not sustain vermin, nor breed or promote fungi or bacteria.
Handling & storage	Isover products are supplied fully palletised, offering the following benefits: <ul style="list-style-type: none"> • Weatherproof packaging for outside storage • Reduced haulage costs • Less handling therefore less damage • Reduced storage space • Packs remain clean and in good condition
Health & safety	A Material Safety Data Sheet can be obtained from the Isover website.
Certification	CE marked (1121-CPD-BA0053) to BS EN 13162. SpecSure Warranty with guaranteed lifetime performance when used in British Gypsum systems.

Customer Service - Order Placement and Enquiries

Tel: 0800 032 2555

Email: isovercustomerservice@saint-gobain.com

Isover Address:

Whitehouse Industrial Estate,
Runcorn, Cheshire, WA7 3DP

Technical Enquiries - Advice and Support Line

Tel: 0115 945 1143

Email: isover.enquiries@saint-gobain.com

isover.co.uk